



















Pegasus

Emergency push buttons \varnothing 22

EN ISO 13850














| | DESCRIPTION | COLOUR | CODE | WEIGHT gr | MIN. PACK QTY. | DIMENSIONS |
|-------------------------------------------------------------------------------------|-----------------------------------------------------------------|-------------------------------------------------------------------------------------|----------|-----------|----------------|---------------------------------------------------------------------------------------|
|  | Mushroom operator \varnothing 30 twist to release |  | PPFN1R3N | 42 | 10 |  |
|  | Mushroom operator with vision \varnothing 30 twist to release |  | PPFN1R3S | 44 | 10 |  |
|  | Mushroom operator \varnothing 40 twist to release |  | PPFN1R4N | 44 | 10 |  |
|  | Mushroom operator with vision \varnothing 40 twist to release |  | PPFN1R4S | 46 | 10 |  |
|  | Mushroom operator \varnothing 60 twist to release |  | PPFN1R6N | 50 | 10 |  |
|  | Mushroom operator with vision \varnothing 60 twist to release |  | PPFN1R6S | 52 | 10 |  |

Pegasus

Emergency push buttons \varnothing 22 EN ISO 13850



AUTOMATION TECHNOLOGIES

| | DESCRIPTION | COLOUR | CODE | WEIGHT gr | MIN. PACK QTY. | DIMENSIONS |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------|-------------------------------------------------------------------------------------|----------|-----------|----------------|---------------------------------------------------------------------------------------|
|  | Mushroom operator \varnothing 40 with key release |  | PPFN1C4N | 76 | 10 |  |
|  | Mushroom operator \varnothing 40 push-pull |  | PPFN1P4N | 44 | 10 |  |
|  | Mushroom operator \varnothing 40 push-pull with vision |  | PPFN1P4S | 46 | 10 |  |
|  | Mushroom operator \varnothing 40 push-pull with colour cap |  | PPFN1P4C | 45 | 10 |  |
| | Mushroom operator \varnothing 40 push-pull with lens cap |  | PPFL1P4N | 45 | 10 | |

TECHNICAL NOTES

- All operators comply with the relevant European standard
- EN ISO 13850 Machine safety Emergency stop operators, functional characteristics - Design guidelines
- IEC/EN60947-5-1
- Comply with the standard IEC/EN60204-1: Machine safety Machine electrical circuits General guidelines
- The push buttons are designed with a load charge mechanism to ensure a reliable operation and stoppage, or blockage, in the activated position. The combination with positive switching NC \ominus contacts and the presence of the "status" indicator on some models, guarantee a high degree of reliability and effectiveness.